



www.keyfire.com

*Manufacturing Excellence
Since 1988*

REEL-LITE

1" Diameter Attack Hose

- **1 year warranty**
- **Abrasion Resistant Cover**
- **Lightweight and Kink Resistant**
- **Heat Resistance**
- **Single Jacket Construction**
- **Chemical Resistance**
- **Specifically designed for skid units**

Are You Really Ready?





Visit us on the Web: www.keyfire.com

Reel-Lite Specification Sheet

- **Lightweight Booster Hose**

A multi-purpose, lightweight, rigid 1" diameter attack hose that meets the needs of industrial, municipal and forestry market applications. This uniquely constructed product features an all polyester cover for heat and abrasion resistance, along with a special helical interior reinforcement to retain its rigid shape. This thin-walled Polyurethane lined hose, is the most durable lightweight booster hose on the market.

▶ **Hose Construction**

Circular woven, single jacket, combined with a helical interior reinforcement, and a polyester cover.

▶ **Tube**

Extruded polyurethane liner for age, ozone and chemical resistance.

▶ **Internal Diameter**

One inch (38 mm)

▶ **Bowl Size**

1 5/16"

▶ **Characteristics**

▶ **Length**

Available in 50' to 200' continuous lengths.

▶ **Couplings**

Field replaceable coupling with a one inch NH thread standard. Aluminum internal expansion ring coupling available upon request.

▶ **Color**

The color shall be red.

- Normal service conditions in temperature range from -30°F to 112°F
- Heat resistant up to 500°F
- UL abrasion test of 10,000 cycles minimum
- Minimum working pressure of 300 PSI
- Service test to 600 PSI
- Maximum burst pressure of 900 PSI
- Pliable and abrasion resistant cover
- Lightweight and kink resistant
- 1-Year warranty against defects in material and workmanship

Contact our sales representatives for more information.

Hose Size	1" (38 mm)
Part Number	RB10-600R
Test Pressure	600 PSI
Weight 50' Coupled	10 LBS
Recommended Reel Size	12" minimum